

Service Vehicle

Standard Features

- Heavy-duty two stage cast iron compressor pump
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Finned intercooler (two stage only)
- Centrifugal unloader (two stage only)
- Oil sight glass
- Each unit is filled with Jenny Synthetic Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- Powder coated ASME certified receivers
- Protectively mounted fittings
- Bucket high manual and bottom mounted tank drain
- Large canister intake filter with replaceable filter elements
- High quality special unloading valves to assist in engine starting
- Stainless steel braided discharge hose
- Tank gauge
- Pressure relief safety valve
- Constant run control
 - Single stage set 105 – 125 PSI
 - Two stage set 145 – 175 PSI
- Pneumatic throttle idle control
- Honda GX Series OHV Engine
- Designed, tested and proven to meet the demands of the construction and rental industry

J11HGA-30T



Single Stage

Model	Pump	HP	Tank Gallon	Drive	CFM @ 125 PSI	CFM @ 150 PSI
K5HGA-30T	K	5	30	Recoil Start	8.6	7.9
GC8HGA-30T	GC	8			16.0	14.9
GC11HGA-30T		11		Electric Start	18.3	17.3
J11HGA-30T	J		20.9		19.8	

K5HGA-30T



Two Stage

Model	Pump	HP	Tank Gallon	Drive	CFM @ 125 PSI	CFM @ 175 PSI
GT5HGB-30T	GT	5	30	Recoil Start	8.6	7.9
GT8HGB-30T		8			16.0	14.9
GT11HGB-30T		11		Electric Start	18.3	17.3
W11HGB-30T	W		19.8		17.6	
U18HGB-80T	U	18	80		39.5	34.7

Options

- Air line filter ■ Lubricator ■ Electric start
- Other engine options available upon request
- Other pressures available upon request

GT11HGB-30T

